



Industrial Range

MODEL

H540



- ▶ Ranges up to 0-1200 bar
- ▶ Supplied with Software
- ▶ Simultaneous display of all measurement data
- ▶ User friendly operation via Menu System

## Hydraulic Comparator for Pressure Calibration

- ▶ Accuracy to 0.025%
- ▶ Power, Read and Store data from test instrument
- ▶ Rechargeable batteries supplied with charger
- ▶ Dual area screwpress for easy prime and pressure control



DH·Budenberg

# Industrial Range

MODEL

# H540

## Hydraulic Comparator for Pressure Calibration

Standard Accuracy to 0.025%.  
Available with UKAS  
Pressure Calibration Certificate.

### RANGES

0-100 bar 0-400 bar  
0-700 bar 0-1200 bar

The 540 family of Calibrators is a powerful range of instruments providing optimum features for industrial users whilst being user friendly and rugged enough for industrial environments. The instruments include high accuracy measurement of pressure along with means of raising and adjusting pressure. In addition to measuring pressure, the units have a range of electrical inputs to enable the calibration of a variety of instruments.

The H540 features a dual area hydraulic screw press which enables rapid priming at low pressure as well as fine adjustment at high pressure, without the need for additional priming pumps. The unit is fitted with a safety valve which prevents overpressure being generated. The base has two loose union instrument connections which allow for the simultaneous calibration of two instruments if required.

### OPERATING FEATURES

- Pressure Units: There are 10 pre-programmed units including bar, mbar, kPa, MPa, PSI, mmHg, inHg, kg/cm<sup>2</sup>, mH<sub>2</sub>O, plus a user defined unit.
- Resolution: The user can select resolution between 4 and 6 significant digits.
- Damping: Variable average time, between 280 msec and 5 seconds.
- Data Storage: 128k memory which can be used for data logging or manual storage.
- Manual Storage: Includes full alphanumeric test instrument and user identification, plus the ability to log instrument data via the keypad.
- Data Logging: The unit can be used as a data logger with reading intervals between 10 seconds and several hours.
- Leak Testing: The unit can be configured to perform leak tests.
- Switch Test: Unit can be used for switch testing, recording the open and closing pressures for a pressure switch.

Note: Due to DH-Budenberg's policy of continuous improvements, specifications are subject to change without notice.

### ACCURACY

- Pressure Measurement: 0.025% of full scale, includes linearity, hysteresis, repeatability and temperature compensation up to 400 bar, 0.05% fsd above 400 bar.
- Electrical Input: Measurement of millivolts (0-100) & volts, ranges 0-10 and 0-30, accuracy 0.02% scale range.  
Measurement of current 0-25 milliamps, accuracy 0.03% scale range.
- Temperature: (with an external Pt100 DIN), accuracy 0.2°C across range -50°C to 100°C.
- Electrical Output: Two power supplies are available for transducers / transmitters only.  
24 volts  $\pm$  10% (maximum 25 milliamps) for transmitters.  
10 volts  $\pm$  1% (maximum 10 milliamps) for transducers.

### SOFTWARE

Units supplied with software which allows upload of all test data and the production of test records, certificates etc. Software can also be used to remotely control the unit to allow remote instrument setup and reading. The software runs under Windows and is a user-friendly flexible package, meeting the needs of the majority of users. In addition, data can be exported from the package for use in a spreadsheet, such as Excel, thus allowing the user full customisation facilities. Connection to a PC via RS232 Port. A connecting lead is supplied.

### ACCESSORIES

There are many accessories which can be supplied for use with Pressure Calibrators. These include liquid/liquid seals and dual gauge stands. DH-Budenberg has extensive experience in the use of Pressure Calibrators and can supply accessories for many applications. A separate catalogue sheet of accessories is available.

### SPARES, REPAIR & RECERTIFICATION

- Comprehensive service and calibration capability of both DH-Budenberg and non DH-Budenberg test equipment.\*
- Dead-weight Testers (working service or full overhaul).\*
- Gauges (all types, all manufacturers).\*
- Portable Calibrators (all manufacturers).\*
- Comparators.\*
- Units available with UKAS Pressure calibration Certificate as an option.
- Certification traceable to National / International Standards as standard.
- Rapid turn-around times and hire items available as a temporary replacement for strategically important plant.

### PACKING DETAILS

1 carton containing complete Tester: 51 x 49 x 30cm. 0.075m<sup>3</sup> Nett 25kg, Gross 27kg.

\* Not covered by our current BS EN ISO9001



DH·Budenberg

DH-Budenberg Ltd.  
PO Box 224, Woodfield Road,  
Altrincham, Cheshire WA14 4FY.  
Tel: 0161 942 4700.  
Fax: 0161 942 4701.  
Email: sales@dh-budenberg.co.uk

DH-Budenberg S.A.  
56, rue des Ecoles,  
93303 Aubervilliers, BP125,  
Cedex, France.  
Tel: 33 (0) 1 48 39 83 00.  
Fax: 33 (0) 1 48 33 65 90.  
Email: dhonline@desgranges.com

DH-Budenberg GmbH.  
Raiffeisenstrasse 2,  
D-63110 Rodgau,  
Germany.  
Tel: 49 (0) 6106 82 940.  
Fax: 49 (0) 6106 82 9417.  
Email: desgranges.support@t-online.de