

Standard Scale Range Pressure Instruments

BOURDON TUBE TYPE PRESSURE GAUGES

| | | | | | |
|----------|-------|------------|----------|-----------|-----------|
| PRESSURE | (Bar) | 0 to 0.6 | 0 to 6 | 0 to 60 | 0 to 600 |
| | | 0 to 1 | 0 to 10 | 0 to 100 | 0 to 1000 |
| | | 0 to 1.6 | 0 to 16 | 0 to 160 | 0 to 1600 |
| | | 0 to 2.5 | 0 to 25 | 0 to 250 | |
| | | 0 to 4 | 0 to 40 | 0 to 400 | |
| VACUUM | | -0.6 to 0 | -1 to 0 | | |
| COMPOUND | | -1 to +0.6 | -1 to +3 | -1 to +9 | -1 to +24 |
| | | -1 to +1.5 | -1 to +5 | -1 to +15 | |

CHEMICAL SEAL TYPE PRESSURE GAUGES

As for Bourdon Tube Type Pressure Gauges. Maximum Range 0 - 600 Bar.

CAPSULE TYPE DRAUGHT RANGE PRESSURE GAUGES

| | | | |
|----------|----------|---------|----------|
| PRESSURE | (M. Bar) | 0 to 10 | 0 to 100 |
| | | 0 to 16 | 0 to 160 |
| | | 0 to 25 | 0 to 250 |
| | | 0 to 40 | 0 to 400 |
| | | 0 to 60 | |

Vacuum and Compound Ranges produced from above standard capsules i.e. -5 to + 5 M. Bar from 0 to 10 M. Bar Capsule minimum span 10 M. Bar.

SCHAFFER DIAPHRAGM TYPE PRESSURE GAUGES

| | | | | |
|----------|----------|----------|-------|----------|
| PRESSURE | (M. Bar) | 0 to 40 | (Bar) | 0 to 0.6 |
| | | 0 to 60 | | 0 to 1 |
| | | 0 to 100 | | 0 to 1.6 |
| | | 0 to 160 | | 0 to 2.5 |
| | | 0 to 250 | | 0 to 4 |
| | | 0 to 400 | | 0 to 6 |
| | | | | 0 to 10 |
| | | | | 0 to 16 |
| | | | | 0 to 25 |

Vacuum and Compound Ranges produced from above standard ranges. Minimum span 40 M.Bar.

Other ranges and dual scale subject to availability. Consult Sales Office.

Specifications and dimensions given in this leaflet represent the state of engineering at the time of printing. Engineering modifications may take place without prior notice.

STEWART-BUCHANAN GAUGES LTD

Sales Office & Manufacturing Facility.

Burnside Industrial Estate, Kilsyth, G65 9JX, SCOTLAND

Tel:- +44 (0)1236 821533

Fax:- +44 (0)1236 824090

E-Mail:- sales@stewarts-group.com

Web Site:- www.stewarts-group.com

Standard Scale Range Temperature Instruments

BIMETAL THERMOMETERS.

| | | | |
|------|--------|--------------|----------|
| TEMP | Deg.C. | -20 to + 40 | 0 to 100 |
| | | -20 to + 60 | 0 to 120 |
| | | -20 to + 120 | 0 to 160 |
| | | -50 to + 50 | 0 to 200 |
| | | -50 to + 100 | 0 to 300 |
| | | 0 to 60 | 0 to 400 |
| | | 0 to 80 | 0 to 500 |
| | | | 0 to 600 |

GAS FILLED THERMOMETERS.

| | | | |
|------|--------|----------------|-----------|
| TEMP | Deg.C. | -100 to + 100* | 0 to 120 |
| | | -100 to + 200* | 0 to 160 |
| | | -100 to + 300* | 0 to 200 |
| | | -20 to + 120 | 0 to 250 |
| | | 0 to 60 | 0 to 300 |
| | | 0 to 80 | 0 to 400 |
| | | 0 to 100 | 0 to 650* |
| | | | |

Other ranges and dual scale subject to availability.

*Additional calibration costs may apply. Consult Sales Office.

Specifications and dimensions given in this leaflet represent the state of engineering at the time of printing.
Engineering modifications may take place without prior notice.

STEWART-BUCHANAN GAUGES LTD

Sales Office & Manufacturing Facility.

Burnside Industrial Estate, Kilsyth, G65 9JX, SCOTLAND

Tel:- +44 (0)1236 821533

Fax:- +44 (0)1236 824090

E-Mail:- sales@stewarts-group.com

Web Site:- www.stewarts-group.com