

Technical Reference – Water Flow Through Schedule 40 Steel Pipe

■ Flow of Water Through Schedule 40 Steel Pipe

Pressure Drop per 100 feet and Velocity in Schedule 40 Pipe for Water at 60 F.																		
Discharge Gallons per Minute	Cubic Velocity		Press.		Press.		Press.		Press.		Press.		Press.		Press.		Press.	
	per Sec.	per Sq. In.	Drop per Sq. In.	Drop per Sq. In.	Drop per Sq. In.	Drop per Sq. In.	Drop per Sq. In.	Drop per Sq. In.	Drop per Sq. In.	Drop per Sq. In.	Drop per Sq. In.	Drop per Sq. In.	Drop per Sq. In.	Drop per Sq. In.	Drop per Sq. In.	Drop per Sq. In.	Drop per Sq. In.	
.2	0.000446	1.13	1.86	0.616	0.359													
.3	0.000668	1.69	4.22	0.924	0.903	0.504	0.159	0.317	0.061	3/4'								
.4	0.000891	2.26	6.98	1.23	1.61	0.671	0.345	0.422	0.086									
.5	0.0011	2.82	10.5	1.54	2.39	0.840	0.539	0.528	0.167	0.301	0.033							
.6	0.00134	3.39	14.7	1.85	3.29	1.01	0.751	0.633	0.240	0.361	0.041							
.8	0.00178	4.52	25.0	2.46	5.44	1.34	1.25	0.844	0.408	0.481	0.102	1"		1-1/4"				
1	0.00223	5.65	37.2	3.08	8.28	1.68	1.85	1.06	0.600	0.602	0.155	0.371	0.048				1-1/2"	
2	0.00446	11.29	134.4	6.16	30.1	3.36	6.58	2.11	2.10	1.20	0.526	0.743	0.164	0.429	0.044			
3	0.00668			9.25	64.1	5.04	13.9	3.17	4.33	1.81	1.09	1.114	0.336	0.644	0.090	0.473	0.043	
4	0.00891			12.33	111.2	6.72	23.9	4.22	7.42	2.41	1.83	1.49	0.565	0.858	0.150	0.630	0.071	
5	0.01114	2"				8.40	36.7	5.28	11.2	3.01	2.75	1.86	0.835	1.073	0.223	0.788	0.104	
6	0.01337	0.574	0.044	2-1/2"		10.08	51.9	6.33	15.3	3.61	3.84	2.23	1.17	1.29	0.309	0.946	0.145	
8	0.01782	0.765	0.073			13.44	91.1	8.45	27.7	4.81	6.60	2.97	1.99	1.72	0.518	1.26	0.241	
10	0.02228	0.956	0.108	0.670	0.046			10.56	42.4	6.02	9.99	3.71	2.99	2.15	0.774	1.58	0.361	
15	0.03342	1.43	0.224	1.01	0.094	3"				9.03	21.6	5.57	6.36	3.22	1.63	2.37	0.755	
20	0.04456	1.91	0.375	1.34	0.158	0.868	0.056	3-1/2"		12.03	37.8	7.43	10.9	4.29	2.78	3.16	1.28	
25	0.05570	2.39	0.561	1.68	0.234	1.09	0.083	0.812	0.041	4"		9.28	16.7	5.37	4.22	3.94	1.93	
30	0.06684	2.87	0.786	2.01	0.327	1.30	0.114	0.974	0.056			11.14	23.8	6.44	5.92	4.73	2.72	
35	0.07798	3.35	1.05	2.35	0.436	1.52	0.151	1.14	0.704	0.882	0.041	12.99	32.2	7.51	7.90	5.52	3.64	
40	0.08912	3.83	1.35	2.68	0.556	1.74	0.192	1.30	0.095	1.01	0.052	14.85	41.5	8.59	10.24	6.30	4.65	
45	0.1003	4.30	1.67	3.02	0.668	1.95	0.239	1.46	0.117	1.13	0.064			9.67	12.80	7.09	5.35	
50	0.1114	4.78	2.03	3.35	0.839	2.17	0.288	1.62	0.142	1.26	0.076	5"		10.74	15.66	7.88	7.15	
60	0.1337	5.74	2.87	4.02	1.18	2.60	0.406	1.95	0.204	1.51	0.107			12.89	22.2	9.47	10.21	
70	0.1560	6.70	3.84	4.69	1.59	3.04	0.540	2.27	0.261	1.76	0.143	1.12	0.047			11.05	13.71	
80	0.1782	7.65	4.97	5.36	2.03	3.47	0.687	2.60	0.334	2.02	0.180	1.28	0.060			12.62	17.59	
90	0.2005	8.60	6.20	6.03	2.53	3.91	0.861	2.92	0.416	2.27	0.224	1.44	0.074	6"		14.20	22.0	
100	0.2228	9.56	7.59	6.70	3.09	4.34	1.05	3.25	0.509	2.52	0.272	1.60	0.090	1.11	0.036	15.78	26.9	
125	0.2785	11.97	11.76	8.38	4.71	5.43	1.61	4.06	0.769	3.15	0.415	2.01	0.135	1.39	0.055	19.72	41.4	
150	0.3342	14.36	16.70	10.05	6.69	6.51	2.24	4.87	1.08	3.78	0.580	2.41	0.190	1.67	0.077			
175	0.3899	16.75	22.3	11.73	8.97	7.60	3.00	5.68	1.44	4.41	0.774	2.81	0.253	1.94	0.102			
200	0.4456	19.14	28.8	13.42	11.68	8.68	3.87	6.49	1.85	5.04	0.985	3.21	0.323	2.22	0.130	8"		
225	0.5013			15.09	14.63	9.77	4.83	7.30	2.32	5.67	1.23	3.61	0.401	2.50	0.162	1.44	0.043	
250	0.557					10.85	5.93	8.12	2.84	6.30	1.46	4.01	0.495	2.78	0.195	1.60	0.051	
275	0.6127					11.94	7.14	8.93	3.40	6.93	1.79	4.41	0.583	3.05	0.234	1.76	0.061	
300	0.6684					13.00	8.36	9.74	4.02	7.56	2.11	4.81	0.683	3.33	0.275	1.92	0.072	
325	0.7241					14.12	9.89	10.53	4.09	8.19	2.47	5.21	0.797	3.61	0.320	2.08	0.083	
350	0.7798							11.36	5.41	8.82	2.84	5.62	0.919	3.89	0.367	2.24	0.095	
375	0.8355							12.17	6.18	9.45	3.25	6.02	1.05	4.16	0.416	2.40	0.108	
400	0.8912							12.98	7.03	10.08	3.68	6.42	1.19	4.44	0.471	2.56	0.121	
425	0.9469							13.80	7.89	10.71	4.12	6.82	1.33	4.72	0.529	2.73	0.136	
450	1.003	10"						14.61	8.80	11.34	4.60	7.22	1.48	5.00	0.590	2.89	0.151	
475	1.059	1.93	0.054							11.97	5.12	7.62	1.64	5.27	0.653	3.04	0.166	
500	1.114	2.03	0.059							12.60	5.65	8.02	1.81	5.55	0.720	3.21	0.182	
550	1.225	2.24	0.071							13.85	6.79	8.82	2.17	6.11	0.861	3.53	0.219	
600	1.337	2.44	0.083							15.12	8.04	9.63	2.55	6.66	1.02	3.85	0.258	
650	1.448	2.64	0.097	12"								10.43	2.98	7.22	1.18	4.17	0.301	
700	1.560	0.112	2.01	0.047								11.23	3.43	7.78	1.35	4.49	0.343	
750	1.671	3.05	0.127	2.15	0.054	14"						12.03	3.92	8.33	1.55	4.81	0.392	
800	1.782	3.25	0.143	2.29	0.061							12.83	4.43	8.88	1.75	5.13	0.443	
850	1.894	3.46	0.160	2.44	0.068	2.02	0.042					13.64	5.00	9.44	1.96	5.45	0.497	

Technical Reference – Water Flow Through Schedule 40 Steel Pipe

Pressure Drop per 100 feet and Velocity in Schedule 40 Pipe for Water at 60 F.

Discharge Gallons per Minute	Press.		Press.		Press.		Press.		Press.		Press.		Press.		Press.		
	Cubic Ft. per Sec.	Velocity Feet per Sec.	Drop Lbs. per Sq. In.	Velocity Feet per Sec.	Drop Lbs. per Sq. In.	Velocity Feet per Sec.	Drop Lbs. per Sq. In.	Velocity Feet per Sec.	Drop Lbs. per Sq. In.	Velocity Feet per Sec.	Drop Lbs. per Sq. In.	Velocity Feet per Sec.	Drop Lbs. per Sq. In.	Velocity Feet per Sec.	Drop Lbs. per Sq. In.	Velocity Feet per Sec.	Drop Lbs. per Sq. In.
900	2.005	3.66	0.179	2.58	0.075	2.13	0.047					14.44	5.58	9.99	2.18	5.77	0.554
950	2.117	3.86	0.196	2.72	0.083	2.25	0.052					15.24	6.21	10.55	2.42	6.09	0.613
1,000	2.228	4.07	0.218	2.87	0.091	2.37	0.057	16"				16.04	6.84	11.10	2.68	6.41	0.675
1,100	2.451	4.48	0.260	3.15	0.110	2.61	0.068					17.65	8.23	12.22	3.22	7.05	0.807
1,200	2.674	4.88	0.306	3.44	0.128	2.85	0.080	2.18	0.042					13.33	3.81	7.70	0.948
1,300	2.896	5.29	0.355	3.73	0.150	3.08	0.093	2.36	0.048					14.43	4.45	8.33	1.11
1,400	3.119	5.70	0.409	4.01	0.170	3.32	0.107	2.54	0.055					15.55	5.13	8.98	1.28
1,500	3.342	6.10	0.466	4.30	0.195	3.56	0.122	2.72	0.063	18"				16.66	5.85	9.62	1.46
1,600	3.565	6.51	0.527	4.59	0.219	3.79	0.138	2.90	0.071					17.77	6.61	10.26	1.66
1,800	4.010	7.32	0.663	5.16	0.276	4.27	0.172	3.27	0.088	2.58	0.050			19.99	8.37	11.54	2.08
2,000	4.456	8.14	0.808	5.73	0.339	4.74	0.209	3.63	0.107	2.87	0.060			22.21	10.3	12.82	2.55
2,500	5.570	10.17	1.24	7.17	0.515	5.93	0.321	4.54	0.163	3.59	0.091	20"				16.03	3.94
3,000	6.684	12.20	1.76	8.60	0.731	7.11	0.451	5.45	0.232	4.30	0.129	3.46	0.075	24"		19.24	5.59
3,500	7.798	14.24	2.38	10.03	0.982	8.30	0.607	6.35	0.312	5.02	0.173	4.04	0.101			22.44	7.56
4,000	8.912	16.27	3.08	11.47	1.27	9.48	0.787	7.26	0.401	5.74	0.222	4.62	0.129	3.19	0.052	25.65	9.80
4,500	10.03	18.31	3.87	12.90	1.60	10.67	0.990	8.17	0.503	6.46	0.280	5.20	0.162	3.59	0.065	28.87	12.2
5,000	11.14	20.35	4.71	14.33	1.95	11.85	1.21	9.08	0.617	7.17	0.340	5.77	0.199	3.99	0.079		
6,000	13.37	24.41	6.74	17.20	2.77	14.23	1.71	10.89	0.877	8.61	0.483	6.93	0.280	4.79	0.111		
7,000	15.60	28.49	9.11	20.07	3.74	16.60	2.31	12.71	1.18	10.04	0.652	8.08	0.376	5.59	0.150		
8,000	17.82			22.93	4.84	18.96	2.99	14.52	1.51	11.47	0.839	9.23	0.488	6.38	0.192		
9,000	20.05			25.79	6.09	21.34	3.76	16.34	1.90	12.91	1.05	10.39	0.608	7.18	0.242		
10,000	22.28			28.66	7.46	23.71	4.61	18.15	2.34	14.34	1.28	11.54	0.739	7.98	0.294		
12,000	26.74			34.40	10.7	28.45	6.59	21.79	3.33	17.21	1.83	13.85	1.06	9.58	0.416		
14,000	31.19					33.19	8.89	25.42	4.49	20.08	2.45	16.16	1.43	11.17	0.562		
16,000	35.65							29.05	5.83	22.95	3.18	18.47	1.85	12.77	0.723		
18,000	40.10							32.68	7.31	25.82	4.03	20.77	2.32	14.36	0.907		
20,000	44.56							36.31	9.03	28.69	4.93	23.08	2.86	15.96	1.12		

For pipe lengths other than 100 feet, the pressure drop is proportional to the length. Thus, for 50 feet of pipe, the pressure drop is approximately one-half the value given in the table ... for 300 feet, three times the given value, etc. Velocity is a function of the cross sectional flow area; thus, it is constant for a given flow rate and is independent of pipe length.



For the Latest Information

Try Our Fax Back System at 1/916/431-6544

On the Internet: www.stiautomationproducts.com E-mail: sales@stiautomationproducts.com

Scientific Technologies Inc.
Automation Products Group ... Providing
tailored solutions for measurement applications.



Water Flow-2

Tel: 1/888/525-7300 • Fax: 1/435/753-7490
www.stiautomationproducts.com • E-mail: sales@stiautomationproducts.com



engineering